
PCB Separator MAESTRO 3E



Technical Data			
Separation type		Component side circular blade Solder side linear blade	
Operation		by hand	
Separation length		max. 450 mm	
Material		FR4, Aluminum	
Temperature/	Operation	+10 - 35°C / 10 - 85%	
Humidity	Storage	-20-+50°C / 10 - 85%	
not condensing	Transport	-20-+50°C / 10 - 85%	
Weight		22 kg	
Dimensions H x D x W		455 x 700 x 350 mm	
Approvals		CE. FCC class A	

Maximum height of components next to the groove.




Increase in external dimensions after separation.

The pre-scored grooves can be interrupted by cutouts with a length of up to approx. 5 mm.

typical 0.2 mm

If components project above the groove, the linear blade needs to be cut out.
In such a case contact us.



MAESTRO 3E separates both small and large pre-scord PCBs. The table and the rest can be continuously adjusted to the most suitable working position.


The slit between the linear blade and the rest can be adjusted to ensure that the side strips fall through and are sorted out.



Safe Operation

The PCB is placed with its pre-scored groove onto the linear blade and the circular blade is then drawn by hand across the PCB.

The clearance between the upper guide and the linear blade is adjustable to ensure that the PCB is only separated in the pre-scored groove.



	Part No.	Description
	8933945	PCB Separator MAESTRO 3E/450
	Content of delivery	PCB Separator Hexagon key 2 mm Operation manual de/en
	Part No.	Accessories
	8970208.001	Dial gauge for MAESTRO 3E/4S
Pos.	Part No.	Spare parts
1 2 3 4	8930509.001 8936615.001 8936614.001 8933394.001	Circular blade FR4 Guide 2 Guide 1 Linear blade 450



- Headquarters in Germany
- cab offices520 partnersin over 80 countries

cab maintains a presence in the world's major economic areas.



Germany

cab Produkttechnik GmbH & Co KG Postfach 1904 76007 Karlsruhe Wilhelm-Schickard-Str. 14 76131 Karlsruhe Telefon +49 721 6626-0 Telefax +49 721 6626-249 www.cab.de info@cab.de

Further partners on request.

France

cab technologies s.a.r.l. 67350 Niedermodern Téléphone +33 388 722 501 www.cab.de/fr info.fr@cab.de

USA

cab Technology Inc.
Tyngsboro MA, 01879
Phone +1 978 649 0293
www.cab.de/us
info.us@cab.de

Asia 亚洲

cab Technology Co, Ltd. **专定比科技股份有限公司** Junghe, Taipei, Taiwan Phone +886 2 8227 3966 www.cab.de/tw

China 中国

info.asia@cab.de

cab (Shanghai) Trading Co., Little (Lip) 7.4 R. 4 Phone +86 21 6236-3161 www.cab.de/cn info.cn@cab.de

This documentation and any translations hereof are the property of cab GmbH & Co KG.

The replication, processing, reproduction or distribution in whole or in parts requires our prior written consent. © Copyright by cab/9008453.

All delivery, design and technical specifications are compiled to the best of our current knowledge and are subject to change without prior notice.